


Stückliste

Sicht auf
Stecker der
ZRE K2526



Halbleiter

U1	28C256 (EEPROM)
U6	GAL22V10
U11	GAL16V8
U10	Z80 PIO PLCC
U7	74HCT08
U8	74HCT05
U12	74HCT03
U2	ATmega162
U4	ADM699
U3	74HCT573
D2	BAT43
T1	PNP-Transistor
U5	TS1117-3.3-223 (3,3V-Regler SOT 223)
M1	WizNet810MJ

Widerstände

R1, R2, R5, R6	220R
R3	2,2k
RN1	2,2k R-Netz 8+1
RN2, RN3	2,2k R-Netz 4+1

Kondensatoren

C1, C2	22pF
C3, C8-C13, C17, C19, C20	100nF (10x)
C15, C16	220µF
C14	22µF

sonstiges

Q1 8 MHz Quarz
Pfostenleiste + Jumper
58 pol. EFS-Stecker winkelprint

Fassungen

- 1 x 32 pol. PLCC
- 1 x 44 pol. PLCC
- 1 x 24 pol.
- 1 x 20 pol.
- 1 x 8 pol.
- 3 x 14 pol.
- 1 x 28 pol. (für Carrier)
- 2 x 20 pol. SIL-Leiste
- 2 x 28 pol. Pfostenbuchsen 2 mm (Wiznet)
- 5 Pin IC-Steckadapter (für Wiznet)

Debug-Interface

U9 MAX202 (SMD)
C4-C6, C21, C22 100nF 6x (0603, SMD)

ISP-Interface

J10 10 pol. Pfostenstecker
D1 BAT43